

2005 GMC C5C042

View this car on our website at eastsideautopartsmi.com/5241781/ebrochure



Our Price **\$0**

Specifications:

Year:	2005
VIN:	1GDG5C1EX5F901372
Make:	GMC
Stock:	5
Model/Trim:	C5C042
Condition:	Pre-Owned
Mileage:	168,346
Drivetrain:	Rear Wheel Drive
Truck Type:	Other

2005 GMC C5C042

Eastside Auto - 231-853-5700 - View this car on our website at eastsideautopartsmi.com/5241781/ebrochure

Our Location :



2005 GMC C5C042

Eastside Auto - 231-853-5700 - View this car on our website at eastsideautopartsmi.com/5241781/ebrochure

Installed Options

Interior

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel, simulated leather- Steering, power - ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console - located next to driver's seat, and two cupholder
- Two sided single common key for doors and ignition
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition- Seat trim, vinyl, Very Dark Pewter
- Seat belt warning indicator
- Radio, Delco AM-FM stereo radio - with coaxial speakers in all door panels
- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Molded vinyl floor covering
- Interior trim, Very Dark Pewter (Requires 69U Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Headlamp warning buzzer
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Electronic engine hour meter- Coat hooks (2) located on cab back panel - Cloth headliner
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning

Exterior

Washable vinyl exterior trim with color matching

- Windshield wipers, intermittent, with pulse washers
- Windows, Solar-Ray tinted - all windows - Steps under cab doors
- Provisions for mounting front license plate- Paint scheme, solid, upper color
- Paint scheme, solid, lower color
- Mirror, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Exterior roof drip moldings- Daytime running lights
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent

Safety

- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel, simulated leather- Steering, power - ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console - located next to driver's seat, and two cupholder
- Two sided single common key for doors and ignition
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition- Seat trim, vinyl, Very Dark Pewter
- Seat belt warning indicator
- Radio, Delco AM-FM stereo radio - with coaxial speakers in all door panels
- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Molded vinyl floor covering
- Interior trim, Very Dark Pewter (Requires 69U Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Headlamp warning buzzer
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Electronic engine hour meter- Coat hooks (2) located on cab back panel - Cloth headliner
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning

Mechanical

- Air cleaner, dry type
- Alternator, AD230 Delco Remy 105-amp maximum (N/A with YW2 wrecker package)
- Battery, single 600 CCA Delphi Freedom 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires LQR gasoline engine) (N/A with ANQ snow plow prep or YW2 wrecker packages)
- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See Front Axle options more details)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See Rear Axle options for more detail)
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Engine, Vortec 8100MD gasoline V8, 225 hp (167 kw) @ 3600 rpm and 350 lb-ft torque (473 N-m) @ 1,200 rpm. - Maximum engine speed 5000 rpm
- Exhaust, single horizontal - passenger side mounted inside frame rail, stainless-steel with gasoline engines, aluminized steel with diesel engines
- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, (Includes 4-piston brake apply calipers) (Requires GZG or GZJ GVWRs)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer) (Requires GZG or GZJ GVWRs)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin, requires R3C front premium highway tread; with R4N Bridgestone requires R3M front all season tread)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Fuel sender assembly. Robust fuel pump
- Fuel tank, single, 25-gallon (95L) fuel capacity - gas or diesel located midship between the frame rails, with fuel fill neck located over top of frame rail (this option uses the mid-frame tank included in the NG6 dual tank option), (Required in YW2 Wrecker Package) (Standard on 60" (152.4 cm) CA), (Optional on all other CA's) MINIMUM OVERHANG = 36" (3 FEET)

- GVWR, 19,500 lbs. (8845 kg) capacity - GCWR limited to 26,000 lb. (11,794 kg)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: may delete transmission PTO gear.)
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 4.78:1, (Available with all rear axles) (G80 rear limited slip differential is not available with this option when in combination of LRY Duramax diesel engine, NB5 single exhaust, and H08 rear axle)
- Rear axle, single speed, 13,500 lbs. (6123 kg) capacity - full floating, includes 2-piston brake applied calipers (Requires GZG or GZJ GVWs)
- Rear shock absorber, 1.375" (35mm)
- Rear suspension, multi-leaf, 15,000 lbs. (6804 kg) capacity (Requires GZG or GZJ GVW with a GL8 rear axle or with H08 rear axle GW2 GVWR package is required)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread; with S4N Bridgestone requires S3M rear all season tread)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Rear wheel drive
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity, (Requires Q82 steel front wheel)
- Road Speed Governor, controlled by the speed rating of the tires ordered. - which will be less than or equal to 85 mph (137 kph); 80 mph (129 kph) with EC9 128" wheelbase/60" CA, ML6 manual transmission and 008 4.88 rear axle ratio; 75 mph (120 kph) with EC9 128" wheelbase/60" CA, M74 automatic transmission and GL8 13,500 lb 75 mph (120 kph) with 245/70R19.5 tires (required for 22,000 to 26,000 lb GVWRs)
- Tethered fuel cap
- Transmission, Allison 1000 Series automatic - with 0.71 overdrive. Torque Rating: 520 lb-ft (705 N-m). Column shift. Base model does not include power take-off gear, to include PTO gear please order with RPO "PTO". Includes transmission-oil cooler located inside radiator and an air-to-oil auxiliary cooler. PTO mounting location on the driver's side.,(N/A with GW2 or GW4 GVWR Sales Packages) With Option PTX, the truck will be equipped with the Allison 1000HS Highway Series transmission. When ordered with option PTO the truck will be equipped with the Allison 1000RDS Rugged Duty Series transmission. When ordered with option YF2 Ambulance Package or with ANM Fire and Rescue Package, the truck will be equipped with the Allison 1000EVS Emergency Vehicle Series transmission.
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 100" (254 cm) CE. Includes a 6mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63 (Requires KYW 75 mph (120 kph) road speed governor with RPO options M74 automatic transmission) (GVW's 18,000 - 19,500 lbs.)

Eastside Auto

eastsideautopartsmi.com

231-853-5700

10951 Apple Ave

Ravenna, MI 49451

© 2023 AutoRevo - All rights reserved. - Powered by AutoRevo