



2007 CHEVROLET C4500 KODIAK MONROE HAULER 6.6L DIESEL 59K MILES MINT

Our Price \$49,500

View this vehicle on our website at njtruckking.com

King of Cars and Trucks

[856-693-3181](tel:856-693-3181)

1229 Broadway , Westville, New Jersey 08093

[Photos](#)

[Details](#)

[Contact](#)



Specifications:

Year:	2007
VIN:	1GBE4E1297F401114
Make:	CHEVROLET C4500 KODIAK MONROE HAULER 6.6L
Model/Trim:	DIESEL 59K MILES MINT
Condition:	Pre-Owned
Body:	Pickup Truck
Exterior:	Gray
Interior:	Gray
Mileage:	59,974
Drivetrain:	Rear Wheel Drive

Vehicle Description

~~ULTRA RARE PRE-EMISSION HAULER WITH EXTREMELY LOW MILES

ONE OF A KIND

2007 CHEVROLET C4500 CREW CAB HAULER

~MONROE~

6.6L DURAMAX TURBO DIESEL

ALLISON AUTOMATIC TRANSMISSION

(59,974 ORIGINAL / ACTUAL MILES)

2-OWNER

CLEAN CARFAX

NO PAINTWORK

NON SMOKER

GARAGE KEPT

100% RUST FREE TRUCK !

METICULOUSLY MAINTAINED

BEST COLOR COMBO

2 SETS OF KEYS

ALL THE OPTIONS !

FIFTH WHEEL AND GOOSENECK SETUP

DUAL TANKS

EXHAUST BRAKE

TRAILER BRAKE CONTROLLER

TINTED GLASS

LED LIGHTS

TO MUCH TO LIST!

EXCELLENT TIRES !!

THIS TRUCK IS IN MINT CONDITION !

YOU WILL NOT FIND A NICER USED HAULER ANYWHERE!

WHY SPEND 100K PLUS ON A NEW TRUCK WHEN YOU CAN OWN THIS ONE FOR HALF AND IT WILL LAST LONGER THEN ANY OF THE

NEW TRUCKS OUT TODAY ! PRE-EMISSION DIESEL ! NO DEF FLUID ! NO CDL REQUIRED !

ORIGINAL OWNERS MANUALS INCLUDED!

WILL NOT LAST !

BEST OF THE BEST

DON'T SNOOZE AND LOSE BECAUSE YOU WILL NOT FIND ANOTHER LIKE IT !

PRE-EMISSION DURAMAX DIESEL

\$49,500

Installed Options

Interior

- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module, (N/A with ZQ2 driver convenience package)
- Rear bench seat- Seat belt warning indicator- Steering wheel, simulated leather
- Steering, power - ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console - located next to driver's seat, and two cupholder
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

Exterior

- Daytime running lamps
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent
- Exterior roof drip moldings
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Mirror, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Paint scheme, solid, lower color, Summit White
- Paint scheme, solid, upper color, Summit White
- Provisions for mounting front license plate- Steps under cab doors
- Windows, Solar-Ray tinted - front windows only; excluding rearside and rear windows
- Windshield wipers, 2-speed and intermittent, with pulse washers

Safety

- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out

Option Packages

Factory Installed Packages

DURAMAX DIESEL 6.6L, 300 HP (223 KW) @ 3000 RPM, 605 LB-FT (820 N-M) TORQUE @ 1600 RPM (Includes KPJ Engine shutdown)	\$7,127
--	---------

Option Packages Total	\$7,127
-----------------------	---------

- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module, (N/A with ZQ2 driver convenience package)
- Rear bench seat- Seat belt warning indicator- Steering wheel, simulated leather
- Steering, power - ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console - located next to driver's seat, and two cupholder
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

Mechanical

- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See Front Axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See Rear Axle options for more detail)
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin, requires R3C front premium highway tread; with R4N Bridgestone requires R3M front all season tread)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity, (Requires Q82 steel front wheel)
- Transmission, Allison 1000 Series 5-speed automatic - with 4th Generation Electronic Controls and 0.71 overdrive. Torque Rating: 620 lb-ft (840 N-m) with shift energy management. Column shift and parking pawl. Base model does not include power take-off gear. To include PTO gear please order with RPO "PTO". PTO mounting location on the drivers side. Includes transmission-oil cooler located inside radiator. With Option PTX, the truck will be equipped with the Allison 1000HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 1000RDS Rugged Duty Series transmission. (N/A with LMM 2007i emission diesel engines)
- Air cleaner, dry type
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with YW2 wrecker package)
- Battery, single 600 CCA Delphi Freedom 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine) (N/A with YW2 Wrecker package)
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Exhaust, single horizontal - passenger side mounted inside frame rail. With Gasoline engines, stainless-steel exhaust. With diesel engines, aluminized steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler.
- Frame, 8mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 824,800 Section Modulus 10.31
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, (Includes 4-piston brake apply calipers)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Fuel sender assembly. Robust fuel pump
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail and a black tethered fuel cap with gasoline engines and a green tethered fuel cap with diesel engines, DRIVER SIDE FILL NECK ONLY. NO AUXILIARY FUEL PORTS (N/A with YW2 Wrecker Package) MINIMUM OVERHANG = 60" (5 FEET)
- GVWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg) NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: may delete transmission PTO gear.)
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 5.13:1 - Not recommended for most applications, (Requires gasoline

engines only)

- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, Includes 2-piston brake applied calipers
- Rear shock absorber - included with tapered leaf and optional with multi-leaf suspensions. (Included with GR2 or GXA rear tapered leaf suspensions)
- Rear stabilizer bar, provides increased load stabilization - improves handling and reduces vehicle roll. Does not adversely affect ride. (Required with taper leaf springs) (Available with multi leaf springs)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear suspension, tapered leaf, 11,000 lbs. (4990 kg) capacity (Requires GS4 rear stabilizer bar and GL4 rear axle)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread; with S4N Bridgestone requires S3M rear all season tread)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Rear wheel drive
- Road speed governor, controlled by the speed rating of the tires ordered which will be less than or equal to 85 mph (137 kph)
- Tethered fuel cap- TranSynd synthetic automatic transmission fluid
- Wheelbase, 169" (429.3 cm) - with 60" (152.4) CA and 121" (307.3 cm) CE. Includes a 8 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 824,800 section Modulus 10.31

King of Cars and Trucks

King of Cars and Trucks

View this car on our website at njtruckking.com/6377108

Website: njtruckking.com

Phone: 856-693-3181

Map: [1229 Broadway, Westville, New Jersey 08093](#)



