

2005 CHEVROLET C4500 KODIAK MONROE HAULER 6.6L DIESEL 93K MILES MINT RARE

View this car on our website at njtruckking.com/6487761/ebrochure



Our Price **\$49,500**

Specifications:

Year:	2005
VIN:	1GBE4E1295F521699
Make:	CHEVROLET C4500 KODIAK
Model/Trim:	MONROE HAULER 6.6L DIESEL 93K MILES MINT RARE
Condition:	Pre-Owned
Body:	Pickup Truck
Exterior:	Yellow
Engine:	DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (702 N-M) TORQUE @ 1600 RPM
Interior:	Black
Mileage:	93,276
Drivetrain:	Rear Wheel Drive

~~ULTRA RARE PRE-EMISSION HAULER WITH EXTREMELY LOW
MILES

ONE OF A KIND

2005 CHEVROLET C4500 CREW CAB HAULER

~MONROE CONVERSION~

6.6L DURAMAX TURBO DIESEL

ALLISON AUTOMATIC TRANSMISSION

(93,276 ORIGINAL / ACTUAL MILES)

CLEAN CARFAX

NON SMOKER

GARAGE KEPT

100% RUST FREE TRUCK !

METICULOUSLY MAINTAINED

BEST COLOR COMBO VERY RARE

2 SETS OF KEYS

ALL THE OPTIONS !

NVD



CVT

NAVIGATION

AIR RIDE TRUCK

DUAL FULL AIR RIDE SEATS

POWER FOLD DOWN REAR BED

SPRAY IN LINER

FULL GOOSENECK SETUP

SPRAY IN BEDLINER

DUAL TANKS

EXHAUST BRAKE

TRAILER BRAKE CONTROLLER

TINTED GLASS

TO MUCH TO LIST!

BRAND NEW TIRES !!

THIS TRUCK IS IN MINT CONDITION !

YOU WILL NOT FIND A NICER USED HAULER ANYWHERE!

WHY SPEND 100K PLUS ON A NEW TRUCK WHEN YOU CAN OWN
THIS ONE FOR HALF AND IT WILL LAST LONGER THEN ANY OF
THE NEW TRUCKS OUT TODAY ! PRE-EMISSION DIESEL ! NO DEF
FLUID ! NO CDL REQUIRED !

WILL NOT LAST !

BEST OF THE BEST

DON'T SNOOZE AND LOSE BECAUSE YOU WILL NOT FIND
ANOTHER LIKE IT !

PRE-EMISSION DURAMAX DIESEL

\$49,500

2005 CHEVROLET C4500 KODIAK MONROE HAULER 6.6L DIESEL 93K MILES MINT RARE
King of Cars and Trucks - 609-504-8808 - View this car on our website at njtrucking.com/6487761/ebrochure

Our Location :



2005 CHEVROLET C4500 KODIAK MONROE HAULER 6.6L DIESEL 93K MILES MINT RARE
King of Cars and Trucks - 609-504-8808 - View this car on our website at njtrucking.com/6487761/ebrochure

Installed Options

Interior

- Seat belt warning indicator- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel, simulated leather- Steering, power - ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console - located next to driver's seat, and two cupholder
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition- Rear bench seat
- Radio, Delco AM-FM stereo radio - with coaxial speakers in all door panels
- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Molded vinyl floor covering
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Headlamp warning buzzer
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Electronic engine hour meter- Coat hooks (2) located on cab back panel - Cloth headliner
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning

Exterior

- Windshield wipers, intermittent, with pulse washers

- windows, solar-ray tinted - front windows only; excluding rear side and rear windows
- Steps under cab doors- Provisions for mounting front license plate
- Paint scheme, solid, upper color, Summit White
- Paint scheme, solid, lower color, Summit White
- Mirror, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Exterior roof drip moldings- Daytime running lights
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent

Safety

- Seat belt warning indicator- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel, simulated leather- Steering, power - ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console - located next to driver's seat, and two cupholder
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition- Rear bench seat
- Radio, Delco AM-FM stereo radio - with coaxial speakers in all door panels
- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Molded vinyl floor covering
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Headlamp warning buzzer
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Electronic engine hour meter- Coat hooks (2) located on cab back panel - Cloth headliner
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning

Mechanical

- Air cleaner, dry type
- Alternator, AD230 Delco Remy 105-amp maximum (N/A with YW2 wrecker package)
- Battery, single 600CCA Delphi Freedom 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires LQR gasoline engine) (N/A with YW2 wrecker packages)
- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See Front Axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See Rear Axle options for more detail)
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Engine, Vortec 8100MD gasoline V8, 225 hp (167 kw) @ 3600 rpm and 350 lb-ft torque (473 N-m) @ 1,200 rpm. - Maximum engine speed 5000 rpm
- Exhaust, single horizontal - passenger side mounted inside frame rail, stainless-steel with gasoline engines, aluminized steel with diesel engines
- Frame, 8mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, (Includes 4-piston brake apply calipers)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin, requires R3C front premium highway tread; with R4N Bridgestone requires R3M front all season tread)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Rear shock absorber, 1.375" (35mm)
- Rear stabilizer bar, provides increased load stabilization - improves handling and reduces vehicle roll. Does not adversely affect ride. Diameter 44mm, (Required with taper leaf springs) (Available with multi leaf springs)
- Rear suspension, tapered leaf, 11,000 lbs. (4990 kg) capacity (Requires GN1 rear stabilizer bar)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin,

requires S3C rear premium highway tread or S3J rear highway traction tread; with S4N Bridgestone requires S3M rear all season tread)

- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Rear wheel drive
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity, (Requires Q82 steel front wheel)
- Road speed governor, controlled by the speed rating of the tires ordered which will be less than or equal to 85 mph (137 kph)
- Tethered fuel cap
- Transmission, Allison 1000 Series automatic - with 0.71 overdrive. Torque Rating: 520 lb-ft (705 N-m). Column shift. Base model does not include power take-off gear. To include PTO gear please order with RPO "PTO". Includes transmission-oil cooler located inside radiator and an air-to-oil auxiliary cooler. PTO mounting location on the driver's side. With Option PTX, the truck will be equipped with the Allison 1000HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 1000RDS Rugged Duty Series transmission.
- Wheelbase, 169" (429.3 cm) - with 60" (152.4) CA and 121" (307.3 cm) CE. Includes a 8 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 824,800 section Modulus 10.31
- Fuel sender assembly. Robust fuel pump
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail, DRIVER SIDE FILL NECK ONLY. NO AUXILIARY FUEL PORTS (N/A with YW2 Wrecker Package) MINIMUM OVERHANG = 60" (5 FEET)
- GVWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: may delete transmission PTO gear.)
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 5.13:1 - Not recommended for most applications, (Requires gasoline engines only)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, Includes 2-piston brake applied calipers

Option Packages

Factory Installed Packages

-
DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (702 N-M) TORQUE @ 1600 RPM
(Includes KPJ Engine shutdown) \$6,946

-
Option Packages Total
\$6,946

King of Cars and Trucks

njtruckking.com

609-504-8808

1022 N Evergreen Ave

Woodbury, New Jersey 08096

© 2019 AutoRevo - All rights reserved. - Powered by AutoRevo