

2006 CHEVROLET KODIAK C4500 4X4 CREW 6.6L DURAMAX PREDEF ONLY 89K MILE WOW RARE

Our Price \$49,900

View this vehicle on our website at njtruckking.com

King of Cars and Trucks

856-693-3181

1229 Broadway, Westville, New Jersey 08093

Photos Details Contact



Specifications:

Year: 2006

VIN: 1GBE4E3266F412602

Make: CHEVROLET KODIAK C4500

Model/Trim: 4X4 CREW 6.6L DURAMAX PREDEF ONLY 89K MILE WOW RARE

Condition: Pre-Owned

Body: Pickup Truck

Exterior: White

Engine: DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 605 LB-FT (820 N-M)

TORQUE @ 1600 RPM

Interior: Gray Mileage: 89,164

Drivetrain: 4 Wheel Drive

Vehicle Description

~ULTRA RARE 4X4 KODIAK~

PRE-DEF DURAMAX DIESEL

! RARE FIND!

2006 CHEVROLET C4500 KODIAK 4X4

(PRE-DEF FLUID!)

6.6L DURAMAX TURBO DIESEL

MONROE CONVERSION PACKAGE

ALLISON AUTOMATIC TRANSMISSION

(ONLY 89,164 ORIGINAL / ACTUAL MILES)

1-OWNER 1-DRIVER

CALIFORNIA RUST FREE TRUCK

CLEAN CARFAX

ALL THE OPTIONS

LEATHER

AIR RIDE CAB

EXHAUST BRAKE

FOLD DOWN REAR SEAT TO BED

ORIGINAL OWNERS MANUALS

LIKE NEW TIRES

THIS TRUCK IS IN EXCELLENT CONDITION!

TRUE HEAD TURNER

LOOKS RUNS AND DRIVES EXCELLENT

ONLY FLAW IS SLIGHT SLIGHT FADING ON BED FENDERS CLEARCOAT

(ONLY VISIBLE IF RIGHT UP ON IT / NO CHIPPING ETC JUST SLIGHT FADE IN COUPLE SPOTS)

WONT FIND ANOTHER LIKE IT! DONT MISS IT!!

VERY RARE FIND

\$49,900

CALL OR TEXT ROB 856-381-6621 WITH ANY QUESTIONS

Installed Options

Interior

- Powerpoints one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out

Option Packages

Factory Installed Packages

DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 605 LB-FT (820 N-M) TORQUE @ 1600 RPM

(Includes KPJ Engine shutdown)

\$7,127

Ontion Packages Total

- Underhood bodybuilder connections accessory power supply Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Provisions for stereo Includes AM/FM antenna, lead wiring for speakers, and separate door chime module, (N/A with ZQ2 driver convenience package)
- Rear bench seat- Seat belt warning indicator- Steering wheel, simulated leather
- Steering, power ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console located next to driver's seat, and two cupholder
- Vinyl door trim panels with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

Exterior

- Daytime running lamps
- Bumper, front, steel, 96" (243.8 cm) wide styled to minimized wall to wall turn diameter painted argent
- Exterior roof drip moldings
- Integral grille and fenders The grille is the same color as hood with single halogen headlamps.
- Mirror, manual, 102" (259 cm) wide load, integral arm, integral convex mirror black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Paint scheme, solid, lower color, Summit White
- Paint scheme, solid, upper color, Summit White
- Provisions for mounting front license plate- Steps under cab doors
- Windows, Solar-Ray tinted all windows
- Windshield wipers, 2-speed and intermittent, with pulse washers

Safety

- Powerpoints one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out
- Underhood bodybuilder connections accessory power supply Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Provisions for stereo Includes AM/FM antenna, lead wiring for speakers, and separate door chime module, (N/A with ZQ2 driver convenience package)
- Rear bench seat- Seat belt warning indicator- Steering wheel, simulated leather
- Steering, power ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console located next to driver's seat, and two cupholder
- Vinyl door trim panels with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

Mechanical

- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See Front Axle options for more detail)

\$7.127

i uunuguu i uu

- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston (See Hear Axle options for more detail)
- Engine, Vortec 8100MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Front tire size, 245/70R19.5G 9090 lbs. (4123 kg) capacity (Requires KYW 75 mph (120 kph) road speed governor)
- Front tread, highway traction
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Rear limited slip differential
- Rear tire size, 245/70R19.5G 17,500 lbs. (7938 kg) capacity (Requires KYW 75 mph (120 kph) road speed governor)
- Rear tread, highway traction
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc 8-hole, 20,000 lbs. (9072 kg) capacity
- Transmission, Allison 1000 Series automatic with 4th Generation Electronic Controls and 0.71 overdrive. Torque Rating: 620 lb-ft (840 N-m) with shift energy management. Column shift and Parking pawl. Base model does not include power take-off gear. To include PTO gear please order with RPO "PTO". PTO mounting location on the drivers side. Includes transmission-oil cooler located inside radiator. With Option PTX, the truck will be equipped with the Allison 1000HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 1000RDS Rugged Duty Series transmission.
- Air cleaner, dry type- Alternator, AD244 Delco-Remy 150-amp maximum
- Battery, single 600 CCA Delphi Freedom 12V 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine) (N/A with ANQ Snow Plow Prep package)
- Cooling, anti-freeze protection temperature -40 degrees F (-40 degrees C)
- Exhaust, single horizontal driver side mounted inside frame rail, stainless-steel with gasoline engines, aluminized steel with diesel engines
- Four-wheel drive
- Frame, 8mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400
 Section Modulus 7.63
- Front axle, 8000 lbs. (3629 kg) capacity Solid drive axle. Up to 45 degree turn angle (Includes 4 piston brake apply calipers) Manual Locking Hubs
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front suspension, tapered leaf, 8000 lbs. (3629 kg) capacity
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Fuel sender assembly. Robust fuel pump
- Fuel tank, single, 40-gallon (151L) fuel capacity gas or diesel, located behind rear axle with fuel fill neck through frame rail, DRIVER SIDE FILL NECK ONLY. NO AUXILIARY PORTS MINIMUM OVERHANG = 60" (5 FEET)
- GVWR, 17,500 lbs. (7938 kg) capacity GCWR limited to 26,000 lb. (11,794 kg) NOTE:
 Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET) check with IRS for quidelines
- Option PTO not required This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: may delete transmission PTO gear.)
- Parking brake, rear in-wheel park brake hand lever operated
- Rear axle ratio, 5.13:1 (Requires HD2 rear axle)
- Rear axle, single speed, Dana S110 13,500 lbs. (6123 kg) capacity full floating, includes
 2-piston brake applied calipers
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear suspension, multi-leaf, 13,500 lbs. (6123 kg) capacity
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Road speed governor, controlled by the speed rating of the tires ordered which will be less than or equal to 75 mph (120 kph) road speed governor
- Tethered fuel cap
- Transfer case, New Venture Gear model NV273 two-speed, electrically actuated, IP mounted switch. (Includes shield)
- Wheelbase, 194" (492.8 cm) with 84" (213.4 cm) CA and 147" (373.4 cm) CE. Includes a 8mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 824,800 Section Modulus 10.31

King of Cars and Trucks

King of Cars and Trucks

View this car on our website at njtruckking.com/6764682

Website: njtruckking.com

Phone: 856-693-3181

Map: 1229 Broadway, Westville, New Jersey 08093

