



2009 GMC TC5500

Sale Price \$27,985

View this vehicle on our website at 2215de71-f467-425e-b70e-351248ec9e4f.autorevo-websites.com



(314) 786-5317

2050 Creve Coeur Mill Road , Maryland Heights, MO 63043

Photos
Details
Contact



Specifications:

Year:	2009
VIN:	1GDE5C1909F411393
Make:	GMC
Stock:	211517D
Model/Trim:	TC5500
Condition:	Pre-Owned
Body:	Pickup Truck
Exterior:	White
Interior:	Gray
Mileage:	49,688
Drivetrain:	Rear Wheel Drive

Vehicle Description

Summary

Used 2009 GMC C5500 C Series ?? Regular Cab 2WD 4x2 near Ellisville, Fenton & Eureka,

Equipment

Good News! This certified CARFAX 1-owner vehicle has only had one owner before you. Our dealership has already run the CARFAX report and it is clean. A clean CARFAX is a great asset for resale value in the future. This delivery truck has a 6.6 liter 8 Cylinder Engine high output engine. This model is rear wheel drive. Front and rear side curtain airbags are included on the vehicle. The high efficiency automatic transmission shifts smoothly and allows you to relax while driving. This GMC C5500 has front air bags that will protect you and your passenger in the event of an accident. With a diesel engine you will be pleased with the power, torque, and fuel efficiency gains. Anti-lock brakes are standard on this GMC C5500. Stay safe with additional front side curtain airbags.

Installed Options

Interior

- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Dome lamp switches included on driver and passenger doors
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Molded vinyl floor covering
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module, (N/A with ZQ2 power convenience option)
- Steering wheel 16"
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Sunshades, passenger side and driver side, cloth-covered - Tachometer
- Trim console - located next to driver's seat, and two cupholder
- Two sided single common key for doors and ignition
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

Exterior

- Daytime running lamps
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter

- painted argent
- Exterior roof drip moldings- Front mud flaps
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Paint scheme, solid, lower color, Summit White
- Paint scheme, solid, upper color, Summit White - Positive door stops
- Provisions for mounting front license plate- Roof marker lamps- Steps under cab doors
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Windshield wipers, 2-speed and intermittent, with pulse washers

Safety

- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Dome lamp switches included on driver and passenger doors
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter vinyl or 69C Very Dark Pewter cloth)
- Molded vinyl floor covering
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module, (N/A with ZQ2 power convenience option)
- Steering wheel 16"
- Stepwell storage areas at each door front and rear. Includes storage cover.
- Sunshades, passenger side and driver side, cloth-covered - Tachometer
- Trim console - located next to driver's seat, and two cupholder
- Two sided single common key for doors and ignition
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

Mechanical

- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See front axle options more details)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See rear axle options for more detail)
- Engine, Vortec 8.1L MD gasoline V8, 325 hp (239 kw) @ 4000 rpm and 450 lb-ft torque (610 N-m) @ 2,800 rpm. - Maximum engine speed 5000 rpm. Oil Level Sensor: Warning sensor for low oil levels
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity, (Requires Q82 steel front wheel)
- Transmission, automatic, Allison 1000 HS/RDS Series 6-speed - With parking pawl and column shift, includes 4th Generation Electronic Controls and 0.61 overdrive. Torque Rating: 660 lb-ft (895 N-m) with shift energy management. Available with a Gross Vehicle Weight up to 19,500 lbs. (8845 kg) and a Gross Combination Weight Rating up to 26,000 lbs. (11,790 kg). To include PTO gear, please order with RPO "PTO". Includes transmission-oil cooler located inside radiator (N/A with ANM Fire and Rescue or YF2 Ambulance Package; N/A with GW2 or GW4 Sales Packages)
- Air cleaner, dry type
- Alternator, AD244 Delco-Remy 150-amp maximum (N/A with YW2 Wrecker package, ANM Fire and Rescue package or YF2 Ambulance package)
- Battery, single, 600 CCA, ACDelco 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires gasoline engine) (N/A with ANQ Snow Plow Prep package or YW2 Wrecker package)
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)
- Exhaust, single horizontal - passenger side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter, with diesel engines, 409 stainless-steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler.
- Frame, 6mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63

- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, includes 4-piston brake apply calipers. Steering Gear Series: ZF8014, (Requires GZG or GZJ GVWRs)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer) (Requires GZG or GZJ GVWRs)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire size, 225/70R19.5F - 7280 lbs. (3302 kg) capacity, (With R4A Goodyear or R4L Michelin, requires R3C front premium highway tread)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Fuel sender assembly. Robust fuel pump
- Fuel tank, single, 25-gallon (95L) fuel capacity - gas or diesel located midship between the frame rails, with fuel fill neck through the frame rail (this option uses the mid-frame tank included in the NG6 dual tank option) Tethered fuel cap is black with gasoline engines, and green un-tethered fuel cap with diesel engines. MINIMUM OVERHANG = 36" (3 FEET) (Required in YW2 Wrecker Package, standard on 60" (152.4 cm) CA), optional on all other CA's)
- GVWR, 19,500 lbs. (8845 kg) capacity - GCWR limited to 26,000 lb. (11,794 kg) or 30,000 lb. with 2350 Series transmissions (MHE/MHD). NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET). A New Law (Highway Transportation Bill HR3) was passed on August 10, 2005 - Check with IRS for guidelines
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: Will delete transmission PTO gear.)
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 5.13:1 (Requires gasoline engine and HD2 or HD1 single speed rear axles)
- Rear axle, single speed, Dana S110 13,500 lbs. (6123 kg) capacity - full floating, Includes 2-piston brake applied calipers. (Requires GZG or GZJ GVWR)
- Rear shock absorber not desired (N/A with tapered leaf springs)
- Rear suspension brackets are riveted to frame in lieu of bolts
- Rear suspension, multi-leaf, 15,000 lbs. (6804 kg) capacity (Requires GZG or GZJ GVW and HD2 single speed rear axle)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Rear wheel drive
- Road Speed Governor, controlled by the speed rating of the tires ordered. - which will be less than or equal to 85 mph (137 kph); 80 mph (129 kph) with EC9 128" wheelbase/60" CA, ML6 manual transmission and 008 4.88 rear axle ratio; 75 mph (120 kph) with EC9 128" wheelbase/60" CA, M74 automatic transmission and HD2 rear axle
- Steering, power - ZF variable ratio power- Tethered fuel cap
- TranSynd synthetic automatic transmission fluid
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 100" (254 cm) CE. Includes a 6mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63 (Requires KYW 75 mph (120 kph) road speed governor with and HD2 13,500 lbs. (6123 kg) capacity rear axle. With Gasoline engines, requires MBV transmission. With Diesel engines, requires MBV, MBW, MHD, MY6 transmission)

Continental Auto Sales

Continental Auto Sales

View this car on our website at 2215de71-f467-425e-b70e-351248ec9e4f.autorevo-websites.com/6938839

Website: 2215de71-f467-425e-b70e-351248ec9e4f.autorevo-websites.com

Phone: (314) 786-5317

Map: [2050 Creve Coeur Mill Road , Maryland Heights, MO 63043](#)

