

# 2005 GMC C4500 KODIAK HAULER DURAMAX DIESEL ONLY 95K MILES MUST SEE

## Our Price \$39,900

View this vehicle on our website at njtruckking.com

King of Cars and Trucks

#### 856-693-3181

1229 Broadway, Westville, New Jersey 08093

Photos Details Contact



# **Specifications:**

Year: 2005

 VIN:
 1GDE4E1235F506056

 Make:
 GMC C4500 KODIAK

Model/Trim: HAULER DURAMAX DIESEL ONLY 95K MILES MUST SEE

Condition: Pre-Owned

Body: Pickup Truck

Exterior: White

Engine: DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (702 N-M)

TORQUE @ 1600 RPM

Interior: Black
Mileage: 95,982

Drivetrain: Rear Wheel Drive

### **Vehicle Description**

**DURAMAX DIESEL C4500 HAULER!** 

2005 GMC C4500 KODIAK / TOPKICK

HAULER BODY

**CREW CAB** 

PRE-DEF!

6.6L DURAMAX TURBO DIESEL

**AUTOMATIC TRANSMISSION** 

(ONLY 95,982 ORIGINAL / ACTUAL MILES)

LOADED!

LEATHER SEATS

POWER FOLD DOWN REAR SEAT TO LAY FLAT

**POWER OPTIONS** 

LIKE NEW TIRES

ALCOA'S

TOOLBOX STORAGE ON BODY

**GOOSENECK BALL** 

**READY TO HAUL!** 

TRUCK IS IN EXCELLENT CONDITION

ALWAYS MAINTAINED

**RUNS AND DRIVES EXCELLENT!** 

MINOR SMALL IMPREFECTIONS DUE TO AGE

WILL NOT LAST!

**BUY IT NOW** 

\$39,900

CALL / TEXT ROB 856-381-6621 WITH ANY QUESTIONS

# **Installed Options**

#### Interior

- Powerpoints one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Radio, Delco AM-FM stereo radio with coaxial speakers in all door panels
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out

Underhead hadubuilder connections accessors newer cumply. Provides 191/ newer

## **Option Packages**

#### **Factory Installed Packages**

DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (702 N-M) TORQUE @ 1600 RPM

(Includes KPJ Engine shutdown)

\$6,946

Option Packages Total

\$6,946

- Ondernood bodybullider confinections accessory power supply Frovides 121 power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering- Rear bench seat- Seat belt warning indicator
- Steering wheel, simulated leather- Steering, power ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console located next to driver's seat, and two cupholder
- Vinyl door trim panels with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

#### **Exterior**

- Daytime running lights
- Bumper, front, steel, 96" (243.8 cm) wide styled to minimized wall to wall turn diameter painted argent
- Exterior roof drip moldings
- Integral grille and fenders The grille is the same color as hood with single halogen headlamps.
- Mirror, manual, 102" (259 cm) wide load, integral arm, integral convex mirror black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Paint scheme, solid, lower color, Summit White
- Paint scheme, solid, upper color, Summit White
- Provisions for mounting front license plate- Steps under cab doors
- Windows, Solar-Ray tinted front windows only; excluding rearside and rear windows
- Windshield wipers, intermittent, with pulse washers

#### Safety

- Powerpoints one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Radio, Delco AM-FM stereo radio with coaxial speakers in all door panels
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster storage in the seat riser with a small lip at the front to stop contents from sliding out
- Underhood bodybuilder connections accessory power supply Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Coat hooks (2) located on cab back panel
- Electronic engine hour meter
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering- Rear bench seat- Seat belt warning indicator
- Steering wheel, simulated leather- Steering, power ZF variable ratio power
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Trim console located next to driver's seat, and two cupholder
- Vinyl door trim panels with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

#### Mechanical

- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston (See Front Axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston (See Rear Axle options for more detail)
- Engine, Vortec 8100MD gasoline V8, 225 hp (167 kw) @ 3600 rpm and 350 lb-ft torque (473 N-m) @ 1,200 rpm.
   Maximum engine speed 5000 rpm
- Front tire size, 225/70R19.5F 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin, requires R3C front premium highway tread; with R4N Bridgestone requires R3M front all season tread)

- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc 8-hole, 20,000 lbs. (9072 kg) capacity. (Requires Q82 steel front wheel)
- Transmission, Allison 1000 Series automatic with 0.71 overdrive. Torque Rating: 520 lb-ft (705 N-m). Column shift. Base model does not include power take-off gear. To include PTO gear please order with RPO "PTO". Includes transmission-oil cooler located inside radiator and an air-to-oil auxiliary cooler. PTO mounting location on the driver's side. With Option PTX, the truck will be equipped with the Allison 1000HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 1000RDS Rugged Duty Series transmission.
- Air cleaner, dry type
- Alternator, AD230 Delco Remy 105-amp maximum (N/A with YW2 wrecker package)
- Battery, single 600CCA Delphi Freedom 12V 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires LQR gasoline engine) (N/A with YW2 wrecker packages)
- Cooling, anti-freeze protection temperature -40 degrees F (-40 degrees C)
- Exhaust, single horizontal passenger side mounted inside frame rail, stainless-steel with gasoline engines, aluminized steel with diesel engines
- Frame, 8mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Front axle, 7000 lbs. (3175 kg) capacity I-beam Wide-trac. Up to 53 degree turn angle, (Includes 4-piston brake apply calipers)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Fuel sender assembly. Robust fuel pump
- Fuel tank, single, 40-gallon (151L) fuel capacity gas or diesel, located behind rear axle
  with fuel fill neck through frame rail, DRIVER SIDE FILL NECK ONLY. NO AUXILIARY
  FUEL PORTS (N/A with YW2 Wrecker Package) MINIMUM OVERHANG = 60" (5 FEET)
- GVWR, 16,500 lbs. (7484 kg) capacity GCWR limited to 24,000 lb. (10,866 kg)
- Option PTO not required This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: may delete transmission PTO gear.)
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 5.13:1 Not recommended for most applications, (Requires gasoline engines only)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity full floating, Includes 2-piston brake applied calipers
- Rear shock absorber, 1.375" (35mm)
- Rear stabilizer bar, provides increased load stabilization improves handling and reduces vehicle roll. Does not adversely affect ride. Diameter 44mm, (Required with taper leaf springs) (Available with multi leaf springs)
- Rear suspension, tapered leaf, 11,000 lbs. (4990 kg) capacity (Requires GN1 rear stabilizer bar)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 225/70R19.5F 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread; with S4N Bridgestone requires S3M rear all season tread)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Rear wheel drive
- Road speed governor, controlled by the speed rating of the tires ordered which will be less than or equal to 85 mph (137 kph)
- Tethered fuel cap
- Wheelbase, 169" (429.3 cm) with 60" (152.4) CA and 121" (307.3 cm) CE. Includes a 8 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 824,800 section Modulus 10.31

King of Cars and Trucks

King of Cars and Trucks

View this car on our website at njtruckking.com/6960703

Website: njtruckking.com Phone: 856-693-3181

Map: 1229 Broadway, Westville, New Jersey 08093

