

# 2005 GMC C4500 KODIAK HAULER DURAMAX DIESEL ONLY 95K MILES MUST SEE

View this car on our website at [njtruckking.com/6960703/ebrochure](http://njtruckking.com/6960703/ebrochure)



Our Price **\$39,900**

## Specifications:

<b>Year:</b>	2005
<b>VIN:</b>	1GDE4E1235F506056
<b>Make:</b>	GMC C4500 KODIAK
<b>Model/Trim:</b>	HAULER DURAMAX DIESEL ONLY 95K MILES MUST SEE
<b>Condition:</b>	Pre-Owned
<b>Body:</b>	Pickup Truck
<b>Exterior:</b>	White
<b>Engine:</b>	DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (702 N-M) TORQUE @ 1600 RPM
<b>Interior:</b>	Black
<b>Mileage:</b>	95,982
<b>Drivetrain:</b>	Rear Wheel Drive

DURAMAX DIESEL C4500 HAULER!

2005 GMC C4500 KODIAK / TOPKICK

HAULER BODY

CREW CAB

PRE-DEF !

6.6L DURAMAX TURBO DIESEL

AUTOMATIC TRANSMISSION

( ONLY 95,982 ORIGINAL / ACTUAL MILES )

LOADED!

LEATHER SEATS

POWER FOLD DOWN REAR SEAT TO LAY FLAT

POWER OPTIONS

LIKE NEW TIRES

ALCOA'S

TOOLBOX STORAGE ON BODY

GOOSENECK BALL

READY TO HAUL!

TRUCK IS IN EXCELLENT CONDITION

ALWAYS MAINTAINED

RUNS AND DRIVES EXCELLENT!

MINOR SMALL IMPREFECTIONS DUE TO AGE

WILL NOT LAST !

BUY IT NOW

\$39,900

CALL / TEXT ROB 856-381-6621 WITH ANY QUESTIONS

2005 GMC C4500 KODIAK HAULER DURAMAX DIESEL ONLY 95K MILES MUST SEE

King of Cars and Trucks - 856-381-6621 - View this car on our website at [njtruckking.com/6960703/ebrochure](http://njtruckking.com/6960703/ebrochure)

### Our Location :



2005 GMC C4500 KODIAK HAULER DURAMAX DIESEL ONLY 95K MILES MUST SEE

King of Cars and Trucks - 856-381-6621 - View this car on our website at [njtruckking.com/6960703/ebrochure](http://njtruckking.com/6960703/ebrochure)

## Installed Options

### Interior

- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Trim console - located next to driver's seat, and two cupholder
- Tachometer with automatic and manual transmissions
- Sunshades, passenger side and driver side, vinyl-covered
- Steering, power - ZF variable ratio power- Steering wheel, simulated leather

Steering, power - ZF variable ratio power- Steering wheel, simulated leather

- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter- Seat belt warning indicator- Rear bench seat
- Radio, Delco AM-FM stereo radio - with coaxial speakers in all door panels
- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Molded vinyl floor covering
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Headlamp warning buzzer
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Electronic engine hour meter- Coat hooks (2) located on cab back panel
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

---

## Exterior

- Paint scheme, solid, upper color, Summit White
- Provisions for mounting front license plate- Steps under cab doors
- Windows, Solar-Ray tinted - front windows only; excluding rearside and rear windows
- Windshield wipers, intermittent, with pulse washers
- Paint scheme, solid, lower color, Summit White
- Mirror, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Exterior roof drip moldings- Daytime running lights
- Bumper, front, steel, 96" (243.8 cm) wide - styled to minimized wall to wall turn diameter painted argent

---

## Safety

- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Cloth headliner- Trim console - located next to driver's seat, and two cupholder
- Tachometer with automatic and manual transmissions
- Sunshades, passenger side and driver side, vinyl-covered
- Steering, power - ZF variable ratio power- Steering wheel, simulated leather
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Seat trim, vinyl, Very Dark Pewter- Seat belt warning indicator- Rear bench seat
- Radio, Delco AM-FM stereo radio - with coaxial speakers in all door panels
- Powerpoints - one in-cab power source (in addition to optional cigarette lighter) for electrical plug-in accessories
- Molded vinyl floor covering
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Headlamp warning buzzer
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Engine "Check Gauges" telltale light and buzzer, oil pressure gauge
- Electronic engine hour meter- Coat hooks (2) located on cab back panel
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pocket on front doors, beverage holders, and reflector on all doors
- Warning tone, key-in-ignition

---

## Mechanical

- Air cleaner, dry type
- Alternator, AD230 Delco Remy 105-amp maximum (N/A with YW2 wrecker package)
- Battery, single 600CCA Delphi Freedom 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C grounded directly to starter, (Requires LQR gasoline engine) (N/A with YW2 wrecker packages)
- Brakes, front, power, 4-wheel disc, 4 channel ABS 4-piston - (See Front Axle options for more detail)
- Brakes, rear, power, 4-wheel disc, 4 channel ABS 2-piston - (See Rear Axle options for more detail)
- Cooling, anti-freeze protection temperature - -40 degrees F (-40 degrees C)

- Engine, Vortec 8100MD gasoline V8, 225 hp (167 kw) @ 3600 rpm and 350 lb-ft torque (473 N-m) @ 1,200 rpm. - Maximum engine speed 5000 rpm
- Exhaust, single horizontal - passenger side mounted inside frame rail, stainless-steel with gasoline engines, aluminized steel with diesel engines
- Frame, 8mm - 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 610,400 Section Modulus 7.63
- Front axle, 7000 lbs. (3175 kg) capacity - I-beam Wide-trac. Up to 53 degree turn angle, (Includes 4-piston brake apply calipers)
- Front shock absorber, diameter 1.375" (35mm)
- Front stabilizer bar, 2" x 2" square tube (5 cm x 5 cm)
- Front suspension, tapered leaf, 7000 lbs. (3175 kg) capacity (includes stabilizer)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire size, 225/70R19.5F - 7280 lbs. (3802 kg) capacity, (With R4A Goodyear or R4L Michelin, requires R3C front premium highway tread; with R4N Bridgestone requires R3M front all season tread)
- Front tread, premium, highway (Requires R4A Goodyear or R4L Michelin)
- Front wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole. 10,000 lbs. (4536 kg) capacity, (Requires Q83 steel rear wheel)
- Fuel sender assembly. Robust fuel pump
- Fuel tank, single, 40-gallon (151L) fuel capacity - gas or diesel, located behind rear axle with fuel fill neck through frame rail, DRIVER SIDE FILL NECK ONLY. NO AUXILIARY FUEL PORTS (N/A with YW2 Wrecker Package) MINIMUM OVERHANG = 60" (5 FEET)
- GVWR, 16,500 lbs. (7484 kg) capacity - GCWR limited to 24,000 lb. (10,866 kg)
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. (Note: may delete transmission PTO gear.)
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 5.13:1 - Not recommended for most applications, (Requires gasoline engines only)
- Rear axle, single speed, 11,000 lbs. (4990 kg) capacity - full floating, Includes 2-piston brake applied calipers
- Rear shock absorber, 1.375" (35mm)
- Rear stabilizer bar, provides increased load stabilization - improves handling and reduces vehicle roll. Does not adversely affect ride. Diameter 44mm, (Required with taper leaf springs) (Available with multi leaf springs)
- Rear suspension, tapered leaf, 11,000 lbs. (4990 kg) capacity (Requires GN1 rear stabilizer bar)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 225/70R19.5F - 13,660 lbs. (6196 kg) capacity, (With S4A Goodyear, requires S3C rear premium highway tread or S3H rear traction tread; with S4L Michelin, requires S3C rear premium highway tread or S3J rear highway traction tread; with S4N Bridgestone requires S3M rear all season tread)
- Rear tread, premium, highway (Requires S4A Goodyear or S4L Michelin)
- Rear wheel drive
- Rear wheels, 19.5" x 6.75" (49.5 cm x 17.1 cm), steel disc - 8-hole, 20,000 lbs. (9072 kg) capacity, (Requires Q82 steel front wheel)
- Road speed governor, controlled by the speed rating of the tires ordered which will be less than or equal to 85 mph (137 kph)
- Tethered fuel cap
- Transmission, Allison 1000 Series automatic - with 0.71 overdrive. Torque Rating: 520 lb-ft (705 N-m). Column shift. Base model does not include power take-off gear. To include PTO gear please order with RPO "PTO". Includes transmission-oil cooler located inside radiator and an air-to-oil auxiliary cooler. PTO mounting location on the driver's side. With Option PTX, the truck will be equipped with the Allison 1000HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 1000RDS Rugged Duty Series transmission.
- Wheelbase, 169" (429.3 cm) - with 60" (152.4) CA and 121" (307.3 cm) CE. Includes a 8 mm 80,000 psi (551,600 kPa) yield strength, steel frame, RBM: 824,800 section Modulus 10.31

## Option Packages

### Factory Installed Packages

-  
 DURAMAX DIESEL 6600, 300 HP (223 KW) @ 3000 RPM, 520 LB-FT (702 N-M) TORQUE @ 1600 RPM  
 (Includes KPJ Engine shutdown)      \$6,946

-  
 Option Packages Total  
 \$6,946

King of Cars and Trucks

[njtrucking.com](http://njtrucking.com)

856-381-6621

1229 Broadway

Westville, New Jersey 08093

© 2022 AutoRevo - All rights reserved. - Powered by [AutoRevo](#)