

northtexasequipment.com
+1 (682) 402-9972
800 Burlington Rd
Fort Worth, TX 76179

North Texas
Equipment

2008 GMC C6500 CHIPPER DUMP TRUCK W/ 11FT BODY

Maria Diaz +1 (682) 402-9972

View this car on our website at northtexasequipment.com/7168913/ebrochure

Our Price **\$29,950**

Specifications:

Year:	2008
VIN:	1GDJ6C1G68F412962
Make:	GMC
Stock:	412962
Model/Trim:	C6500 CHIPPER DUMP TRUCK W/ 11FT BODY
Condition:	Pre-Owned
Exterior:	Orange
Engine:	8.1L V8 GAS
Interior:	Tan
Mileage:	120,823
Drivetrain:	Rear Wheel Drive
Truck Type:	Dump - Box

2008 GMC C6500 CHIPPER DUMP TRUCK

*11FT BODY

2HYD OUTRIGGERS

8.1L GAS

MANUAL TRANSMISSION

120K MILES

#412962

THIS 2008 GMC C6500 CHIPPER DUMP LANDSCAPE TRUCK 11-FOOT BODY 2 PASSENGER WITH RIDER CAB THAT SEATS 3 OR GREAT STORAGE V-8 GAS 6 SPEED WITH POWER STEERING NON-CDL IS IDEAL FOR TREE TRIMMING APPLICATIONS. THIS TRUCK HAS 2 HYDRAULIC OUTRIGGERS FOR STABILITY AND HAS A 6 YARD DUMP BED FOR DEBRIS AND CHIPPER APPLICATIONS. THIS 2008 GMC C6500 11 FOOT CHIPPER DUMP TRUCK NON CDL 120K MILES FEATURES A 8.1 LITRE 8cyl GASOLINE ENGINE. IT IS EQUIPMED WITH A 6 SPEED MANUAL TRANSMISSION. THIS VEHICLE IS ORANGE WITH A TAN INTERRIOR.

FINANCING AVAILABLE!!

NATION WIDE DELIVERY AVAILABLE!!

NEED A SHIPPING QUOTE? HAVE ANY QUESTIONS?

CALL OR TEXT ANYTIME:

MARIA 682-402-9972 (HABLO ESPAÑOL)

TIM 817-819-6319

2008 GMC C6500 CHIPPER DUMP TRUCK W/ 11FT BODY

North Texas Equipment - +1 (682) 402-9972 - View this car on our website at northtexasequipment.com/7168913/ebrochure

Our Location :



2008 GMC C6500 CHIPPER DUMP TRUCK W/ 11FT BODY

North Texas Equipment - +1 (682) 402-9972 - View this car on our website at northtexasequipment.com/7168913/ebrochure

Installed Options

Interior

- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Center console - located next to driver's seat and two cupholders - Cloth headliner
- Coat hooks (2) located on cab back panel - Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 driver convenience package)
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, High-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out
- Seat, passenger, High-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel 16" - Stepwell storage areas at each door. Includes storage cover
- Sunshades, passenger side and driver side, cloth-covered - Tachometer
- Two sided single common key for doors and ignition
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Warning tone, key-in-ignition

Exterior

- Bumpers, front steel, painted argent - Bumper thickness 3.9 mm - Daytime running lamps

- Exterior roof drip moldings- Front mud flaps
- Horn, single electric mounted inside engine compartment
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps. Entry steps under cab doors are based upon fuel tank type
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5cm x 17.8 cm) with 6" x 7" (15.2cm x 17.8cm) convex section
- Paint, solid, lower color, Summit White- Paint, solid, upper color, Summit White
- Positive door stops- Provisions for mounting front license plate- Roof marker lamps
- Steps under cab doors
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Windshield wipers, 2-speed and intermittent, with pulse washers

Safety

- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Center console - located next to driver's seat and two cupholders - Cloth headliner
- Coat hooks (2) located on cab back panel - Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 driver convenience package)
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, High-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out
- Seat, passenger, High-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel 16"- Stepwell storage areas at each door. Includes storage cover
- Sunshades, passenger side and driver side, cloth-covered - Tachometer
- Two sided single common key for doors and ignition
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Warning tone, key-in-ignition

Mechanical

- Air cleaner, dry-type standard filter element (Requires gasoline engine)
- Alternator, AD244, Delco-Remy 150-amp maximum (Requires gasoline engine)
- Battery, single AC Delco, 600 CCA, 12V. - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C, (Requires gasoline engine)
- Brake system, hydraulic, split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" (391mm) rotor diameter, 1 1/2" (39.1 mm) rotor thickness with (4) 2 1/2" (64 mm) diameter pistons with 8,000 lb. (3629 kg) front axle, (70 mm) diameter pistons with 10,000 lb. (4536 kg) front axle
- Engine, Vortec 8.1L MD gasoline V8, 295 hp (220 kw) @ 3600 rpm and 440 lb-ft (594 N-m) torque @ 3,200 rpm - Oil Level Sensor: Warning sensor for low oil levels
- Exhaust system, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic convertor, with diesel engines 409 stainless-steel exhaust system, integrated oxidation catalyst on Isuzu engine, Diesel Particulate Filter (DPF) and exhaust gas cooler (N/A with FQT wheelbase with Isuzu diesel engines and not available with EG9 wheelbase with Caterpillar engine)
- Frame, painted semi-gloss black 6mm rail - 50,000 psi (344,750 kPa) yield strength, steel frame, SAE J1392-050XLK steel, dimensions 9 1/2" x 3" x 1/4" section modulus 9.58 cu. in., RBM 479,000
- Front axle, 8000 lbs. (3629 kg) capacity - Up to 53 degree turn angle. Steering Gear Series: ZF8014
- Front shock absorber, diameter 1.375" (35mm)
- Front suspension, tapered leaf, 8000 lbs. (3629 kg) capacity (Requires FM8 front axle)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire size, 245/75R22.5G - 9350 lbs. (4241 kg) capacity, (With R4A Goodyear requires R3C front premium tread; N/A with Michelin)
- Front tire tread, premium highway
- Front wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E- Coat), 13,220 lbs. (5996 kg) capacity, (Requires QH4 rear wheels)
- Fuel tank, single, 50-gallon (189.2L) fuel capacity - driver side, steel top tread plate, sump, drain and steps under cab on front passenger side. Provides clean back of cab and a black tethered fuel cap with gasoline engines, and a brass tethered fuel cap with diesel engines (Requires QH4, RPR or RNN 22.5" wheels; N/A with GPG Lo-Pro option)
- Option PTO not required - This option should only be ordered when a customer specifically

- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. NOTE: Deletes transmission PTO gear with Allison MTX/MBZ 2200HS, MTY 2300HS, MHE 2350HS, MPS 2500HS, and MPQ 2550HS Series transmissions.
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 6.50:1 (Requires HD1 or HPK single speed rear axle)
- Rear axle, single-speed, Dana S16-130-S, 15,000 lbs. (6804 kg) capacity - 40,000 lbs. (18,144 kg) GCWR
- Rear suspension, multi-leaf, 15,000 lbs. (6804 kg) capacity (Requires HD1 single speed rear axle)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 245/75R22.5G - 17,640 lbs. (8001 kg) capacity (With S4A Goodyear requires S3C rear premium tread or S3H rear highway traction tread; N/A with Michelin)
- Rear tire tread, premium highway- Rear wheel drive
- Rear wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat) 26,440 lbs. (11,993 kg) capacity, (Requires HPK or HD1 single speed rear axle or HPM two-speed rear axle and 22.5" tires)
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" tires have speed governed to a maximum of 75 mph (120 kph). A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company's specifications for details.
- Steering, power - ZF variable ratio power
- Transynd synthetic automatic transmission fluid (Available with automatic transmissions only)
- Transmission, automatic, Allison 2300 HS/RDS Series (Close Ratio) 5-speed - No parking pawl. Includes 4th Generation Electronic Controls and 0.71 overdrive. Torque rating: 450 lb-ft (610 N-m), Available with a Gross Vehicle Weight up to 33,000 lbs. (15,000 kg) and a Gross Combined Weight up to 33,000 lbs. (15,000 kg). When "PTX" is selected, it does not include power take-off gear in the Allison 2300 HS Highway Series transmission. To include PTO gear please order with RPO "PTO" for Allison 2300 RDS Rugged Duty Series transmission. Includes transmission oil cooler in radiator, increased cooling and column shift. (Requires gasoline engine, HD1 or HPK single speed rear axles)
- Truck application NOTE: Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET) - check with IRS for guidelines
- Underhood air cleaner restriction gauge
- Wheelbase, 128" (325.1 cm) - with 60" (152.4 cm) CA and 135.3" (343.7 cm) CE. Includes a 6 mm 50,000 psi (344,750 kPa) yield strength, steel frame, RBM: 479,000 Section Modulus 9.58 cu. in. (N/A with diesel engine)

Option Packages

Factory Installed Packages

-

VORTEC 8.1L MD GASOLINE V8, 295 HP
 (220 KW) @ 3600 RPM, 440 LB-FT
 (594 N-M) TORQUE @ 3,200 RPM
 Oil Level Sensor: Warning sensor
 for low oil levels

financing is provided by outside companies. payments rates and down payment is per finance company. With Approved Credit

North Texas Equipment
northtexasequipment.com
 +1 (682) 402-9972
 800 Burlington Rd
 Fort Worth, TX 76179

© 2023 AutoRevo - All rights reserved. - Powered by AutoRevo