

northtexasequipment.com
+1 (682) 402-9972
800 Burlington Rd
Fort Worth, TX 76179

North Texas
Equipment

2009 GMC C7500 60' ALTEC FORESTRY BUCKET TRUCK W/ 11' BOX BODY

Maria Diaz +1 (682) 402-9972

View this car on our website at northtexasequipment.com/7179121/ebrochure



Our Price **\$49,950**

Specifications:

Year: 2009
VIN: 1GDJ7C1G49F404972
Make: GMC
Stock: 404972
Model/Trim: C7500 60' ALTEC FORESTRY BUCKET TRUCK W/ 11' BOX BODY
Condition: Pre-Owned
Exterior: Orange
Engine: 8.1L V8 GAS
Interior: Tan
Mileage: 89,700
Drivetrain: Rear Wheel Drive
Truck Type: Bucket, Boom

2009 GMC C7500 60' ALTEC FORESTRY BUCKET TRUCK

60' ALTEC BOOM

*11FT BODY

2HYD OUTRIGGERS

8.1L V8 GAS

MANUAL TRANSMISSION

89K MILES

#404972

THIS 2009 GMC C7500 60' ALTEC FORESTRY BUCKET TRUCK, IT'S 60' ALTEC BUCKET / BOOM SYSTEM HAS OVER-CENTER CAPABILITY AND IS MOUNTED BEHIND THE CAB FOR, IDEAL FOR TREE TRIMMING APPLICATIONS. THIS TRUCK HAS 2 HYDRAULIC OUTRIGGERS FOR STABILITY AND HAS A 6 YARD DUMP BED FOR DEBRIS AND CHIPPER APPLICATIONS.

FINANCING AVAILABLE!!
NATION WIDE DELIVERY AVAILABLE!!
NEED A SHIPPING QUOTE? HAVE ANY QUESTIONS?
CALL OR TEXT ANYTIME:

MARIA 682-402-9972 (HABLO ESPAÑOL)

TIM 817-819-6319

2009 GMC C7500 60' ALTEC FORESTRY BUCKET TRUCK W/ 11' BOX BODY

North Texas Equipment - +1 (682) 402-9972 - View this car on our website at northtexasequipment.com/7179121/ebrochure

Our Location :



2009 GMC C7500 60' ALTEC FORESTRY BUCKET TRUCK W/ 11' BOX BODY

North Texas Equipment - +1 (682) 402-9972 - View this car on our website at northtexasequipment.com/7179121/ebrochure

Installed Options

Interior

- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Center console - located next to driver's seat and two cupholders - Cloth headliner
- Coat hooks (2) located on cab back panel
- Dome lamp switches included on driver and passenger doors
- Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out.
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel 16"
- Stepwell storage areas at each door front and rear. Includes storage cover
- Sunshades, passenger side and driver side, vinyl-covered - Tachometer
- Two sided single common key for doors and ignition
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Warning tone, key-in-ignition

Exterior

- Bumpers, front steel, painted argent - Bumper thickness 3.9 mm - Daytime running lamps
- Exterior roof drip moldings- Front mud flaps
- Horn, single electric mounted inside engine compartment
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps. Entry steps under cab doors are based upon fuel tank type
- Mirrors, manual, 102" (259 cm) wide load, integral arm, integral convex mirror - black molded composite 12" x 7" (30.5 cm x 17.8 cm) with 6" x 7" (15.2 cm x 17.8 cm) convex section
- Paint, solid, lower color, Summit White- Paint, solid, upper color, Summit White
- Positive door stops- Provisions for mounting front license plate- Roof marker lamps
- Steps under cab doors
- Windows, Solar-Ray tinted. Light tinted windshield and side window glass with light transmissivity of 70%
- Windshield wipers, 2-speed and intermittent, with pulse washers

Safety

- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Center console - located next to driver's seat and two cupholders - Cloth headliner
- Coat hooks (2) located on cab back panel
- Dome lamp switches included on driver and passenger doors
- Electronic engine hour meter
- Engine "Check gauges" telltale light and buzzer, oil pressure gauge
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Headlamp warning buzzer
- Interior trim, Very Dark Pewter (Requires 69V Very Dark Pewter Vinyl or 69C Very Dark Pewter Cloth)
- Molded vinyl floor covering
- Powerpoints - two in-cab power sources (in addition to optional cigarette lighter) for electrical plug-in accessories
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module (N/A with ZQ2 power convenience option)
- Seat trim, vinyl, Very Dark Pewter
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out.
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Steering wheel 16"
- Stepwell storage areas at each door front and rear. Includes storage cover
- Sunshades, passenger side and driver side, vinyl-covered - Tachometer
- Two sided single common key for doors and ignition
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Warning tone, key-in-ignition

Mechanical

- Air cleaner, dry-type standard filter element (Requires gasoline engine)
- Alternator, AD244, Delco-Remy 150-amp maximum (Requires gasoline engine)
- Battery, single, 600 CCA, ACDelco 12V - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C, (Requires gasoline engine)
- Brake system, hydraulic, split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" (391mm) rotor diameter, 1 1/2" (39.1 mm) rotor thickness with (4) 2 1/2" (64 mm) diameter pistons with 8,000 lb. (3629 kg) front axle, (70 mm) diameter pistons with 10,000 lb. (4536 kg) front axle
- Engine, Vortec 8.1L MD gasoline V8, 295 hp (220 kw) @ 3600 rpm, 440 lb-ft (594 N-m) torque @ 3,200 rpm. - Oil Level Sensor: Warning sensor for low oil levels NOT AVAILABLE FOR PRODUCTION AFTER DECEMBER 2008
- Exhaust system, single horizontal - driver side mounted inside frame rail, with gasoline engine stainless-steel exhaust with catalytic converter. With diesel engines 409 stainless-steel exhaust system, integrated oxidation catalyst on Isuzu diesel, Diesel Particulate Filter (DPF) and exhaust gas cooler. (N/A with FQT wheelbase with Isuzu diesel engines)
- Frame, painted semi-gloss black 6mm rail - 50,000 psi (344,750 kPa) yield strength, steel frame, SAE J1392-050XLK steel, dimensions 9 1/2" x 3" x 1/4" section modulus 9.58 cu. in., RBM 479,000
- Front axle, 10,000 lbs. (4536 kg) capacity - Up to 53 degree turn angle. Steering Gear Series: ZF8016
- Front shock absorber, diameter 1.375" (35mm)
- Front suspension, tapered leaf, 10,000 lbs. (4536 kg) capacity (Requires FM8 or FM6 front axle)
- Front tire manufacturer code, Goodyear (Requires S4A Goodyear)
- Front tire size, 245/75R22.5G - 9350 lbs. (4241 kg) capacity, (With R4A Goodyear requires R3C front premium tread; N/A with Michelin)
- Front tire tread, premium highway

- Front tire tread, premium highway
- Front wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat), 13,220 lbs. (5996 kg) capacity, (Requires QH4 rear wheels; N/A with FL3 front axle)
- Fuel tank, single, 50-gallon (189.2L) fuel capacity - driver side, steel top tread plate, sump, drain and steps under cab on front passenger side. Provides clean back of cab and a black tethered fuel cap with gasoline engines, and a brass tethered fuel cap with diesel engines
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions. NOTE: Deletes transmission PTO gear with Allison MTX/MBZ 2200HS, MTY 2300HS, MHE 2350HS, MPS 2500HS, and MPQ 2550HS Series transmissions.
- Parking brake, hand lever operated transmission mounted drum brake
- Rear axle ratio, 7.17:1 (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle or HPM, H15 two-speed rear axle)
- Rear axle, single-speed, Dana 19060S, 19,000 lbs. (8618 kg) capacity - includes 75W-90 synthetic lubricant and National brand oil seals (Requires GN0, GN2, GN8, GR9, GP1, GP0 or G40 rear suspension) (N/A with FL3 front axle)
- Rear suspension, multi-leaf, 19,000 lbs. (8618 kg) capacity (Requires HPK or HPL single rear axle or HPM two-speed rear axle)
- Rear tire manufacturer code, Goodyear (Requires R4A Goodyear)
- Rear tire size, 245/75R22.5G - 17,200 lbs. (7802 kg) capacity (With S4A Goodyear requires S3C rear premium tread or S3H rear highway traction tread; N/A with Michelin)
- Rear tire tread, premium highway- Rear wheel drive
- Rear wheels, 22.5" x 7.5" (58.9 cm x 19 cm), steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" (28.5 cm) bolt circle, painted Gray (E-Coat) 26,440 lbs. (11,993 kg) capacity, (Requires HPK, HPL, HPN, HPP or HPT single speed rear axle, or HPM, H15 or H25 two-speed rear axle) (Not available with YWM, YWP or YRN 22.5" rear tires)
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" and 24.5" tires have speed governed to a maximum of 75 mph (120 kph). A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company specifications for details.
- Steering, power - ZF variable ratio power
- TranSynd synthetic automatic transmission fluid (Available with automatic transmissions only)
- Transmission, automatic, Allison 2300 HS/RDS Series (Close Ratio) 5-speed - No parking pawl. Includes 4th Generation Electronic Controls and 0.71 overdrive. Torque rating: 450 lb-ft (610 N-m), Available with a Gross Vehicle Weight up to 33,000 lbs. (15,000 kg) and a Gross Combined Weight up to 33,000 lbs. (15,000 kg). When "PTX" is selected, it does not include power take-off gear in the Allison 2300 HS Highway Series transmission. To include PTO gear please order with RPO "PTO" for Allison 2300 RDS Rugged Duty Series transmission. Includes transmission oil cooler in radiator, increased cooling and column shift. (Requires gasoline engine and HPK, HPL, HPM, HPN, HPP or H15 rear axles)
- Truck application NOTE: Federal Excise Tax (FET) of 12% must be paid on the final selling price for trucks with GVWR's of 33,001 lbs. and above. Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax (FET) - check with IRS for guidelines. PLEASE NOTE: The 12% FET tax is NOT included in AutoBook Pricing.
- Underhood air cleaner restriction gauge
- Wheelbase, 140" (355.6 cm) - with 72" (182.9 cm) CA and 135.3" (343.7 cm) CE, (With diesel engine requires NPY exhaust)

Option Packages

Factory Installed Packages

-
 VORTEC 8.1L MD GASOLINE V8, 295 HP
 (220 KW) @ 3600 RPM, 440 LB-FT
 TORQUE (594 N-M) @ 3200 RPM
 Oil Level Sensor: Warning sensor
 for low oil levels

financing is provided by outside companies. payments rates and down payment is per finance company. With Approved Credit

North Texas Equipment
northtexasequipment.com
 +1 (682) 402-9972
 800 Burlington Rd
 Fort Worth, TX 76179

© 2023 AutoRevo - All rights reserved. - Powered by AutoRevo